**PAT-NO:** 

JP357124027A

**DOCUMENT-**

JP 57124027 A

**IDENTIFIER:** 

TITLE:

MOTORCYCLE WITH ENGINE WITH TURBO-

SUPERCHARGER

**PUBN-DATE:** 

August 2, 1982

## **INVENTOR-INFORMATION:**

**NAME** 

**COUNTRY** 

INOUE, KAZUO OTSUKA, TSUNEO

## **ASSIGNEE-INFORMATION:**

NAME

**COUNTRY** 

HONDA MOTOR CO LTD N/A

**APPL-NO:** 

JP56009174

APPL-DATE: January 24, 1981


INT-CL (IPC): F02B037/02, B60K013/04, F01N007/08

## **ABSTRACT:**

PURPOSE: To reliably control supercharged pressures in a motorcycle on which an engine with a turbo-supercharger is mounted, by respectively connecting the first and the second muffler at the lower and upstream sides of the supercharger turbine.

CONSTITUTION: An exhaust gas from an exhaust pipe 8 passes through a turbine T via a common exhaust pipe 15 to force a turbine wheel 18 to drive a compressor wheel 20 and is thereafter released into atmosphere via the first muffler 161. In this operation, if a pressure at an outlet of a compressor C is increased over a specified value, a control valve 24 is appropriately opened and some of an exhaust gas fed into an exhaust manifold 14 is thereby allowed to bypass the turbine T through a waste pipe 23 and then released from the second muffler 162. Thereby, a revolution speed of the turbine is reduced to decrease a supercharged pressure. Thus, as the exhaust gas is released from the second muffler 162, supercharged pressure control may be reliably performed without any effect on back pressures of the turbine.

COPYRIGHT: (C)1982,JPO&Japio



第 2 図

